



TECHNICAL DATA SHEET

DESCRIPTION

TEAM CC BACK SEAL is a water based impregnation emulsion **to reduce water, oil and grease absorption** on the back side (reverse side) of the marble. This product has

1. Good depth of penetration.
2. Resistant to alkalis.
3. Quick development of absorption reduction.

APPLICATION

TEAM CC BACK SEAL is used in the marble industry as an **absorption reduction coat**. It reduces absorption of water, oil and grease. This product can be used for all types of stones and marbles.

APPLICATION PROCEDURE

Application is to be done **before fixing** of stone. Clean and dry the surface. This is very important for proper impregnation of the material. **Mix well before use.**

A brush or a clean cotton cloth can be used for application. It can also be sprayed on the surface. Avoid application in direct sunlight.

A second wet-on-wet coat is recommended if the absorption of the surface is high, like incase of sand-stones and cemented surface. Remove any excess material.

Always prepare a sample before full application to check for final appearance and absorption rate.

Full effect is generated after 24 hours. During this time the surface should remain free of moisture and dust. Aggressive chemical and high pressure washing can destroy the protective effect.

PHYSICAL PROPERTIES

COLOR: Milky white. **COVERAGE:** 12 to 15 mt sq depending on the absorption capacity of substrate.

STORAGE

Store in a cool and a dark place, in an air tight packing. The material is usable for 12 months.



HAZARDS

The use of safety products like gloves, glasses and mask is recommended, specially during spraying. Protect surfaces nearby not to be coated. Avoid harm to third parties. Do not inhale vapors. If used indoors then ensure proper ventilation. Keep out of reach of children.

TEAMCC