

# TECHNICAL DATA SHEET

#### **DESCRIPTION**

TEAM CC CRYSTAL is gel type two-part unsaturated polyester resin based adhesive. This product has

- 1. High shear strength
- 2. Neutral color
- 3. Resistant to abrasive chemicals after curing
- 4. Excellent shine after polishing
- 5. Excellent color depth
- 6. Thin joints

#### **APPLICATION**

TEAM CC CRYSTAL is used in the marble industry as a **adhesive for joining stones** both natural and artificial. Due to **good shear strength** this product is recommended for vertical applications.

# **APPLICATION PROCEDURE**

<u>Clean and dry</u> the surfaces to be bonded. Use on moist surface does not allow proper curing of joint.

Mix both the components in **the ratio of 100:3**. The mixing should be proper. **Mix small quantities** at a time. Using more or less quantity of hardener can lead to a soft bond and discoloring.

At the time of mixing color can be used to <u>match the stone color</u>. Special attention to color matching should be given when applied to white stones. In case of white stone, we recommend sealing 2 inches on each side of the joint with TEAM EPOXY PLUS 1009. This will <u>reduce color variation and chipping</u>.

This mix is workable for about 20 minutes.

The joint should be left for 12 hours before working on the joints. Colder temperature can delay the curing process. During this time **keep the joint free of dust and moisture**.



# **PHYSICAL PROPERTIES**

COLOR: Neutral

DENSITY: 1.23 g/cc

HARDNESS: 90 "Shore D"

BENDING STRENGTH: 70-80 N/mm sq.

TENSIL STRENGTH: 45-55 N/mm sq.

#### **STORAGE**

Store in a cool and a dark place in air tight packing. The material is usable for 6 months.

# **HAZARDS**

The use of safety products like gloves, glasses and mask is recommended, specially during spraying. Protect surfaces nearby not to be coated. Avoid harm to third parties. Do not inhale vapors. If used indoors then ensure proper ventilation. **Keep out of reach of children**.