



TECHNICAL DATA SHEET

DESCRIPTION

TEAM CC WEATHER COAT is a water-based impregnation coat to reduce water, oil, grease absorption. This product has

1. Non-yellowing
2. No tackiness during and after drying
3. Anti-graffiti character
4. Application is easy
5. Reduces absorption

APPLICATION

TEAM CC WEATHER COAT is used in the marble industry as a **absorption reduction coat**. It reduces absorption of water and reduces staining by oil and grease. This product can be used for all types of stones and marbles **specially sand stone** in both external and internal applications.

APPLICATION PROCEDURE

Clean and dry the surfaces. This is very important for proper impregnation of the material. Shake well before use.

A brush or a clean cotton cloth can be used for application. It can also be sprayed on the surface. Avoid application in direct sunlight.

A second wet-on-wet coat is recommended if the absorption of the surface is high, like in case of sand-stone and cemented surface. **Excess coat can lead to staining like white spots**. Therefore, remove any excess material.

Always **prepare a sample** before full application to check for final appearance and absorption rate.

Full effect is generated after 24 hours. During this time the surface should remain free of moisture and dust. Aggressive chemical and high-pressure washing can destroy the protective effect.



PHYSICAL PROPERTIES

COLOR: Transparent

DENSITY: 1

COVERAGE: 12 to 20 mt sq depending on the absorption capacity of substrate.

STORAGE

Store in a cool and a dark place in air tight packing. The material is usable for 12 months.

HAZARDS

The use of safety products like gloves, glasses and mask is recommended, specially during spraying. Protect surfaces nearby not to be coated. Avoid harm to third parties. Do not inhale vapors. If used indoors then ensure proper ventilation. Keep out of reach of children.